

PRODUCT DATA SHEET

NORGLASS LABORATORIES PTY.LTD.

A.B.N. 92 001 807 245

P.O. Box 312, Neutral Bay. NSW 2089 Australia

59 Moxon Road, Punchbowl NSW

Ph: 61 2 9708 2200 Fax: 61 2 9796 3069

Email: norglass@bigpond.net.au

www.norglass.com.au



PRODUCT: SLIP RESISTANT AGENT

DESCRIPTION: A uniform granular polypropylene particle for increasing traction in coatings.

USES: Stairs, Paths, Ramps, Driveways, pool areas.

PROPERTIES (at 20°C)

COLOUR: White Powder

TOXICITY: Non Hazardous Substance

FINISH: Textured

COVERAGE: 50g per litre of paint

DRYING TIME: N/A Refer to coating specification

RECOATING: N/A Refer to coating specification

POT LIFE: N/A Refer to coating specification

MIXING RATIO: 50g per litre in paint – 15g per litre in clears

THINNING: N/A Refer to coating specification

WEIGHT/LITRE: 410 grams/Litre

VOLUME SOLIDS: N/A

FLASH POINT: N/A

CLEAN UP: As specified for the coating medium

U.N. NUMBER: N/A

DESCRIPTION:	A granulated powder to provide traction when mixed into low sheen or matt paint/clear finishes. Note. Do not add this product to gloss finishes as the result will be extremely slippery when wet. Norglass Slip Resistant Agent will not settle after mixing but should be stirred before application. At the rate of 50 grams per litre the texture will be optimized, but more or less can be added as desired. When used in clear coatings the ratio of 15 grams per litre should not be exceeded. At that ratio it will not detract from the clear finish.
PREPARATION:	Refer to the coating specification
DIRECTIONS FOR USE:	Mix the powder into the paint/clear slowly, and continue stirring until thoroughly blended. Then pour into a paint tray. Use a short nap paint roller for best results. Confine the use of a paint brush to edges only.
APPLICATION:	To be added to the selected coating in the determined ratio
TRANSPORTATION:	N/A
PRECAUTIONS:	N/A
FIRST AID:	N/A
SPECIAL INSTRUCTIONS:	N/A