

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: Weatherfast Deck Paint

 Item Code:
 8100

 UN No:
 1263

Product Use: Paint on Concrete, Fibrous Sheeting & Timber

Air Dry Enamel applied by brush roller or spray, in

accordance with product data sheet.

Restriction of Use: Refer to Section 15

Australian Supplier: **Norglass Paints**Address: 59 Moxon Road

Punchbowl NSW 2196

Australia

Telephone: +61 2 9708 2200 Email: info@norglass.com.au

New Zealand Supplier: xxx Address: xxx xxx

Telephone: 0508 724687

Emergency Numbers:

Australia: 13 1126 (Poisons Information Centre)
New Zealand: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 10 December 2018 v2

Section 2. Hazards Identification

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

New Zealand:

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval No:

Surface Coatings and Colourants (Flammable, Toxic [6.7]) - HSR002669

Pictograms









Flammable

Irritant

Chronic

Ecotoxic

Signal Word: DANGER

Product Name: Weatherfast Deck Paint Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 10 December 2018 Prepared by: Technical Compliance Consultants (NZ) Ltd Tel: 64 9 475 5240 www.techcomp.co.nz

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
3.1C	H226	Flammable liquid and vapour.	Flam. Liq. 3
6.1E (asp)	H305	May be harmful if swallowed and enters airways.	Asp. Tox. 1
6.3A	H315	Causes skin irritation.	Skin Irrit. 2
6.4A	H319	Causes serious eye irritation.	Eye Irrit. 2A
6.5B	H317	May cause an allergic skin reaction.	Skin Sens. 1
6.7B	H351	Suspected of causing cancer.	Carc. 2
6.9A	H372	Causes damage to organs through prolonged or repeated exposure.	STOT RE 1
9.1B	H411	Toxic to aquatic life with long lasting effects.	Aquatic Chronic 2
9.2C	H423	Harmful to the soil environment.	

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing fumes or vapours.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing.
P281	Use personal protective equipment as required.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 +	IF ON SKIN (or hair): Remove/Take off immediately all contaminated
P361+P353	clothing. Rinse skin with water/shower.
P305 +	IF IN EYES: Rinse cautiously with water for several minutes. Remove
P351+P338	contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, foam for extinction.

Storage Code	Storage Statement	
P405	Store locked up.	
P403 + P235	Store in a well-ventilated place. Keep cool.	

Disposal Code	Disposal Statement	
P501	Dispose of according to Local Regulations or Authorities	

Product Name: Weatherfast Deck Paint
Date of SDS: 10 December 2018

Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Urethane Alkyd Resin	40-45	Proprietary
Pigments	30-35	Proprietary
White spirits	12-15	64742-88-7
Additives various	<5%	Proprietary

Section 4.	First Aid Measures

Routes of Exposure:

If in Eyes Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.. If eye irritation persists: Get

medical advice.

If on Skin Wash with plenty of soap and water. Take off contaminated clothing and

wash before re-use. If skin irritation or rash occurs: get medical

advice/attention.

If Swallowed Rinse mouth. DO NOT induce vomiting. If the victim is conscious give

water or milk to drink to dilute the effect. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek immediate medical attention.

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen

remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if

breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion: Not applicable. **Inhalation:** Not applicable.

Skin: Causes skin irritation. May cause an allergic skin reaction.

Eye: Causes serious eye irritation.

Chronic: May be fatal if swallowed and enters airways. Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure.

Section 5. Fire Fighting Measures

Hazard Type	Flammable liquid and vapours can explode if ignited.
Hazards from combustion products	Burning may produce carbon monoxide and carbon dioxide.
Suitable Extinguishing media	Foam, carbon dioxide or dry chemicals.
Precautions for firefighters and special protective clothing	Wear full body protection and self-contained breathing apparatus.
HAZCHEM CODE	3Y

Section 6. Accidental Release Measures

Personal precautions:

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

Product Name: Weatherfast Deck Paint Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 10 December 2018 Prepared by: Technical Compliance Consultants (NZ) Ltd Tel: 64 9 475 5240 www.techcomp.co.nz

Environmental precautions:

Do not discharge into drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Notify authorities if product enters sewers or public waters.

Spill and Disposal procedures:

Extinguish all sources of ignition. Spilt material should be absorbed into dry inert material such as sand, earth or sawdust and disposed by incineration by approved agent or local regulations.

Section 7. Handling and Storage

Precautions for Handling:

- Read label before use.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid breathing fumes or vapours.
- Keep container tightly closed.
- Wash hands thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Avoid release to the environment.
- Wear protective clothing.
- Use personal protective equipment as required.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Store locked up, in a well-ventilated place. Keep cool.
- Product should be stored in properly sealed containers, if at all, not used in one application.
- Keep out of reach of children.
- Do not obliterate label instructions on partly used containers.
- Partly used containers should be properly sealed to avoid spillage.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA ppm	mg/m³	STEL ppm	mg/m³
White Spirit	150	790		

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2017 9TH EDITION.

Engineering Controls

Local exhaust ventilation is usually required. Provide explosion proof ventilation system.

Personal Protection Equipment:



Eyes Wear safety goggles with side shields.

Product Name: Weatherfast Deck Paint Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 10 December 2018 Prepared by: Technical Compliance Consultants (NZ) Ltd Tel: 64 9 475 5240 www.techcomp.co.nz

Hands and	Wear neoprene rubber gloves. Wear overalls and use barrier cream.	
Skin		
Respiratory	Avoid breathing solvent vapours by wearing organic vapour	
	respirators.	

Section 9 **Physical and Chemical Properties**

Appearance	White or coloured viscous liquid	
Odour	Low solvent odour	
Odour Threshold Not applicable		
pH	Not applicable	
Boiling Point	150°C for solvent	
Melting Point	Not applicable	
Freezing Point	Not applicable	
Flash Point	32°C	
Flammability	Not applicable	
Upper and Lower	Not applicable	
Exposure Limits		
Volatile Component	Not available	
Vapour Pressure 25°C	Not applicable	
Specific Gravity	1.120 - 1.220	
Solubilities	Insoluble	
Partition Coefficient:	Not applicable	
Auto-ignition	Not applicable	
Temperature		
Decomposition	Not applicable	
Temperature		
Kinematic Viscosity	Not applicable	
Particle Characteristics	Not applicable	

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Conditions to Avoid	Sources of ignition. Heat.
Incompatible Materials	None known.
Hazardous Decomposition	None known.
Products	

Section 11 **Toxicological Information**

Acute Effects:

Swallowed	May cause irritation of mouth, throat and digestive system, resulting in nausea and vomiting.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Causes severe eye irritation.
Skin	Causes skin irritation. May cause an allergic skin reaction.

Chronic Effects:

Carcinogenicity	Suspected of causing cancer.	
Reproductive	Not applicable	
Toxicity		
Germ Cell	Not applicable.	
Mutagenicity		
Aspiration	May be fatal if swallowed and enters airways.	
STOT/SE	Causes damage to organs through repeated or prolonged exposure.	
	Avoid prolonged exposure to solvent vapours.	

Prepared by: Technical Compliance Consultants (NZ) Ltd Tel: 64 9 475 5240 www.techcomp.co.nz Product Name: Weatherfast Deck Paint

Date of SDS: 10 December 2018

STOT/RE Not applicable.

Section 12. Ecotoxicological Information

New Zealand:

HSNO Classes: 9.1B = Toxic to aquatic life with long lasting effects.

9.2C = Harmful to the soil environment.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method: Place recovered product into an appropriate waste container for disposal

through appropriate waste company or specialized landfill in accordance with local regulations. Ensure container is sealed and isolated away from

ignition sources.

Precautions: Ensure waste container containing recovered product is labelled "Hazardous

Waste – Flammable, Ecotoxic". If triple rinsing container, add rinsate to waste

container for disposal.

Disposal methods to avoid: Do not allow to enter waterways.

Section 14 Transport Information

This product is classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code) (7th edition).

This product is classified as a Dangerous Good for transport in NZ; NZS 5433:2012



Road and Rail Transport

UN No: 1263
Class-primary 3
Packing Group III
Proper Shipping Name: PAINT

Air Transport

UN No: 1263
Class-primary 3
Packing Group III
Proper Shipping Name: PAINT

Marine Transport

UN No: 1263
Class-primary 3
Packing Group III
Proper Shipping Name: PAINT

Limited Quantities Statement:

If the product's individual container is below 5L/kg, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

Product Name: Weatherfast Deck Paint Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 10 December 2018 Prepared by: Technical Compliance Consultants (NZ) Ltd Tel: 64 9 475 5240 www.techcomp.co.nz

Section 15 Regulatory Information

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

<u>NOT</u> Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

New Zealand:

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Surface Coatings and Colourants (Flammable, Toxic [6.7]) - HSR002669

HSNO Classification: 3.1C, 6.1E(asp), 6.3A, 6.4A, 6.5B, 6.7B, 6.9A, 9.1B, 9.2C

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	500L (>5L), 1500L(<5L), 250L open
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000L(3.1C, 9.1B)
Emergency Response Plan	1000L(9.1B)
Secondary Containment	1000L(9.1B)
Restriction of Use	Only use for the intended purpose.

Section 16	Other Information
Glossary	
EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms
	inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible
	authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

Australia:

- 1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
- 2. National Industrial Chemicals Notification and Assessment Scheme (NICNAS).
- 3. Standard for the Uniform Scheduling of Medicines and Poisons.
- 4. Australian Code for the Transport of Dangerous Goods by Road & Rail.
- 5. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
- 6. Workplace exposure standards for airborne contaminants, Safe work Australia.
- 7. American Conference of Industrial Hygienists (ACGIH).
- 8. Globally Harmonised System of Classification and Labelling of chemicals.

New Zealand:

- 1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
- 2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
- Assigning a hazardous substance to a HSNO Approval (Aug 2013).

Product Name: Weatherfast Deck Paint Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 10 December 2018 Tel: 64 9 475 5240 www.techcomp.co.nz

- 4. Transport of Dangerous goods on land NZS 5433:2012
- 5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 10 December 2018 Review Date: 10 December 2023

Product Name: Weatherfast Deck Paint Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 10 December 2018 Prepared by: Technical Compliance Consultants (NZ) Ltd Tel: 64 9 475 5240 www.techcomp.co.nz