

NORSYSTEM BOAT EPOXY RESIN (SLOW HARDENER) APR 2021

PRODUCT DATA SHEET

NORGLASS LABORATORIES PTY.LTD.

A.B.N. 92 001 807 245

P.O. Box 312, Neutral Bay. NSW 2089 Australia

59 Moxon Road, Punchbowl NSW

Ph: 61 2 9708 2200 Fax: 61 2 9796 3069

Email: norglass@bigpond.net.au

www.norglass.com.au



NORSYSTEM BOAT EPOXY RESIN (SLOW HARDENER)

DESCRIPTION: A slow setting Hardener for warmer areas.

USES: Laminating timbers with composite reinforcing materials gluing, filling and

fairing.

PROPERTIES (at 20°C)

COLOUR: Clear when mixed with Norsystem Base

TOXICITY: See precautions

FINISH: Clear

COVERAGE: Varies according to uses

CURE TO SOLID: 20-24 hours when mixed with Norsystem Base

POT LIFE @22°C

FOR 100MLS: 1 hour- 1 Hour and 15mins (When mixed)

MIXING RATIO: 1:3 by volume

THINNING: Not recommended

WEIGHT/LITRE: 0.970 kg

VOLUME SOLIDS: 100%

FLASH POINT: < 100°C

CLEAN UP: Norglass Epoxy Thinner

U.N. NUMBER: 2735

PREPARATION: Refer to NORGLASS REINFORCING GUIDE for use.

APPLICATION: Varies according to methods used.

Mixing ratio is 3 parts by volume of Norsystem Base with 1 part by volume of Norsystem Slow or Fast Hardener. **Thorough stirring is essential**. Allow 5-10 minutes for induction then add the extenders selected or pour into a shallow paint tray for laminating. Apply by squeegee, spatula or short nap roller for the

chosen application.

TRANSPORTATION: Hazchem Code: N/A.

Dangerous goods class: Not applicable.

Sizes: 1.5 Litre, 750 ml, 250 ml

PRECAUTIONS: Mild skin irritant. Some allergic reactions can occur. If this happens, cease using

immediately. Wear protective clothing at all times. Provide adequate ventilation

during use.

FIRST AID: If poisoning occurs call a doctor or Poisons Information Centre (Aust) on 13 11 26

or (NZ) 0800 764 766 and have label information ready.

If swallowed DO NOT induce vomiting. Give large quantities of water or milk. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and consult a doctor. Remove contact lenses if present and easy to do and continue rinsing. If skin contact causes irritation, remove contaminated clothing and wash skin thoroughly. If breathing difficulty arises remove to fresh air. Apply

artificial respiration if not breathing.

FIRST AID: If swallowed do not induce vomiting. Give water to drink and seek medical

attention.

If in eyes irrigate with running water for 15 minutes or until irritation subsides and

seek medical attention.

If inhaled, remove to fresh air. If difficulty breathing is experienced give oxygen or

artificial respiration and seek medical advice.

SPECIAL

INSTRUCTIONS: Crush empty containers and send to landfill. Liquid residue to be mixed with sand

before going to land fill.