

# **SAFETY DATA SHEET**

#### Section 1. Identification of the material and the supplier

Product: **Staybond Epoxy Glue Base** 

Item Code: 1001

Product Use: Adhesive when used along with Staybond Glue Hardener

Restriction of Use: Refer to Section 15

Australian Supplier: **Norglass Paints** Address:

59 Moxon Road

Punchbowl NSW 2196

Australia

+61 2 9708 2200 Telephone: Email: info@norglass.com.au

New Zealand Supplier: XXX Address: XXX XXX

Telephone: 0508 724687

**Emergency Numbers:** 

Australia: 13 1126 (Poisons Information Centre) **New Zealand:** 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 15 November 2018 v2

#### Section 2. **Hazards Identification**

#### Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

#### **New Zealand:**

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

## EPA Approval No: Surface Coatings and Colourants (subsidiary) - HSR002670

# **Pictograms**







Irritant

Chronic

**Ecotoxic** 

Signal Word: **DANGER** 

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
6.1E (asp)	H304	May be fatal if swallowed and enters airways.	Asp. Tox. 2
6.3A	H315	Causes skin irritation.	Skin Irrit. 2
6.4A	H319	Causes serious eye irritation.	Eye Irrit. 2A

Product Name: Staybound Epoxy Glue Base Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 15 November 2018 Tel: 64 9 475 5240 www.techcomp.co.nz

Page 1

6.5B	H317	May cause an allergic skin reaction.	Skin Sens. 1
6.9B	H373	May cause damage to organs through prolonged or repeated exposure.	STOT RE 2
9.1B	H411	Toxic to aquatic life with long lasting effects.	Aquatic Chronic 2

<b>Prevention Code</b>	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P260	Do not breathe dust, fume, gas, mist or vapours.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 +	IF IN EYES: Rinse cautiously with water for several minutes. Remove
P351+P338	contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use carbon dioxide, foam or dry chemicals for extinction.

Storage Code	Storage Statement
P405	Store locked up.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

# Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
High Viscosity Bisphenol a Liquid Resin	70	25068-38-6
Low Viscosity Liquid Epoxy Resin	24	Proprietary
Additives	Up to 100	Proprietary

## Section 4. First Aid Measures

#### Routes of Exposure:

If in Eyes Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice.

If on Skin Wash with plenty of soap and water. Take off contaminated clothing and

wash before re-use. If skin irritation or rash occurs: get medical

advice/attention.

If Swallowed Rinse mouth. DO NOT induce vomiting. If the victim is conscious give

water or milk to drink to dilute the effect. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips

to prevent vomit entering the lungs. Seek medical attention.

Product Name: Staybound Epoxy Glue Base Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 15 November 2018 Prepared by: Technical Compliance Consultants (NZ) Ltd Tel: 64 9 475 5240 www.techcomp.co.nz

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen

remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if

breathing becomes difficult.

### Most important symptoms and effects, both acute and delayed

Symptoms:

**Ingestion:** Not applicable. **Inhalation:** Not applicable.

**Skin:** Causes skin irritation. May cause an allergic skin reaction.

**Eye:** Causes serious eye irritation.

**Chronic:** May be fatal if swallowed and enters airways.

May cause damage to organs through prolonged or repeated exposure.

## Section 5. Fire Fighting Measures

Hazard Type	Non Flammable Liquid
Hazards from combustion products	Under thermal degradation decomposition products are mainly phenolic compounds. Carbon monoxide and carbon dioxide.
Suitable Extinguishing media	Extinguishing media carbon dioxide, foam or dry chemicals.
Precautions for firefighters and special protective clothing	Firefighters should wear self-contained breathing apparatus.
HAZCHEM CODE	3Z

#### Section 6. Accidental Release Measures

### **Personal precautions:**

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

# **Environmental precautions:**

Do not discharge into drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Notify authorities if product enters sewers or public waters.

#### Spill and Disposal procedures:

Extinguish all sources of ignition. Spilt material should be absorbed into dry inert material such as sand, earth or sawdust and disposed by incineration by approved agent or local regulations.

#### Section 7. Handling and Storage

#### **Precautions for Handling:**

- Read label before use.
- Do not breathe dust, fume, gas, mist or vapours.
- Wash hands thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Avoid release to the environment.
- Wear protective clothing.

#### **Precautions for Storage:**

- Store away from incompatible materials listed in Section 10.
- Store locked up.
- Store in a cool place. Keep containers closed.
- · Keep out of reach of children.

## Section 8 Exposure Controls / Personal Protection

#### WORKPLACE EXPOSURE STANDARDS (provided for quidance only)

Product Name: Staybound Epoxy Glue Base
Date of SDS: 15 November 2018

Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

## Substance

No ingredients have known exposure limits.

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2017 9TH EDITION.

## **Engineering Controls**

Use only in well ventilated areas. Introduce local exhaust ventilation if necessary.

## **Personal Protection Equipment**



Eyes	Wear safety goggles.
Hands and Skin	Wear chemical resistant gloves. Wear overalls and use barrier cream.
Respiratory	Avoid breathing vapour or dust by wearing approved respirators.

## **Section 9** Physical and Chemical Properties

Appearance	Viscous Translucent Cream
Odour	Pine odour
Odour Threshold	Not applicable
pH	Not applicable
<b>Boiling Point</b>	Not applicable
Melting Point	Not applicable
Freezing Point	Not applicable
Flash Point	>200°C
Flammability	Not applicable
Upper and Lower	Not applicable
<b>Exposure Limits</b>	
Volatile Component	Not applicable
Vapour Density	Not applicable
Specific Gravity	1.100
Solubilities	Insoluble
Partition Coefficient:	Not applicable
Auto-ignition	Not applicable
Temperature	
Decomposition	Not applicable
Temperature	
Kinematic Viscosity	Not applicable
<b>Particle Characteristics</b>	Not applicable

## Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.	
Conditions to Avoid Avoid excessive heating.		
Incompatible Materials	Avoid acid bases amines and oxidising materials.	
<b>Hazardous Decomposition</b>	Under thermal degradation decomposition products are mainly	
Products	phenolic compounds. Carbon monoxide and carbon dioxide.	

Section 11	Toxicological	Information
------------	---------------	-------------

Product Name: Staybound Epoxy Glue Base Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 15 November 2018 Prepared by: Technical Compliance Consultants (NZ) Ltd Tel: 64 9 475 5240 www.techcomp.co.nz

Page 4

#### **Acute Effects:**

Swallowed	Not applicable.	
Dermal	Not applicable.	
Inhalation	Not applicable.	
Eye	Causes serious eye irritation.	
Skin	Causes skin irritation. May cause an allergic skin reaction.	

#### **Chronic Effects:**

Carcinogenicity	Not applicable.
Reproductive	Not applicable.
Toxicity	
Germ Cell	Not applicable.
Mutagenicity	
Aspiration	May be fatal if swallowed and enters airways.
STOT/SE	Not applicable.
STOT/RE	Causes damage to organs through prolonged or repeated exposure.

### **Section 12. Ecotoxicological Information**

#### **New Zealand:**

HSNO Classes: 9.1B = Toxic to aquatic life with long lasting effects.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available
Precautions	Do not allow to enter waterways.

## **Section 13. Disposal Considerations**

**Disposal Method:** Place recovered product into an appropriate waste container for disposal through appropriate waste company or specialized landfill in accordance with local regulations.

**Precautions:** Ensure waste container containing recovered product is labelled "Hazardous Waste – Ecotoxic". If triple rinsing container, add rinsate to waste container for disposal.

**Disposal methods to avoid:** Do not allow to enter waterways.

### Section 14 Transport Information

This product is classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code) (7th edition).

This product is classified as a Dangerous Good for transport in NZ; NZS 5433:2012



Road and Rail Transport

UN No: 3082 Class-primary 9 Packing Group III

Product Name: Staybound Epoxy Glue Base Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 15 November 2018 Prepared by: Technical Compliance Consultants (NZ) Ltd Tel: 64 9 475 5240 www.techcomp.co.nz

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S

Air Transport

UN No: 3082
Class-primary 9
Packing Group III

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S

Marine Transport

UN No: 3082
Class-primary 9
Packing Group III

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S

## **Limited Quantities Statement:**

If the product's individual container is below 5L/kg, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

## Section 15 Regulatory Information

#### Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a **Schedule 5** Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

#### **New Zealand:**

**UEL** 

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Surface Coatings and Colourants (subsidiary) - HSR002670

HSNO Classification: 6.1E(asp), 6.3A, 6.4A, 6.5B, 6.9B, 9.1B

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	Not required
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000L(9.1B)
Emergency Response Plan	1000L(9.1B)
Secondary Containment	1000L(9.1B)
Restriction of Use	Only use for the intended purpose.

#### Section 16 Other Information Glossary $EC_{50}$ Median effective concentration. **EEL** Environmental Exposure Limit. **EPA Environmental Protection Authority HSNO** Hazardous Substances and New Organisms. **HSW** Health and Safety at Work. Lethal concentration that will kill 50% of the test organisms $LC_{50}$ inhaling or ingesting it. Lethal dose to kill 50% of test animals/organisms. $LD_{50}$ LEL Lower explosive level. **OSHA** American Occupational Safety and Health Administration. TEL Tolerable Exposure Limit. TLV Threshold Limit Value-an exposure limit set by responsible

Product Name: Staybound Epoxy Glue Base Date of SDS: 15 November 2018 Prepared by: Technical Compliance Consultants (NZ) Ltd Tel: 64 9 475 5240 www.techcomp.co.nz

Upper Explosive Level

authority.

#### References:

#### Australia:

- 1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
- 2. National Industrial Chemicals Notification and Assessment Scheme (NICNAS).
- 3. Standard for the Uniform Scheduling of Medicines and Poisons.
- 4. Australian Code for the Transport of Dangerous Goods by Road & Rail.
- 5. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
- 6. Workplace exposure standards for airborne contaminants, Safe work Australia.
- 7. American Conference of Industrial Hygienists (ACGIH).
- 8. Globally Harmonised System of Classification and Labelling of chemicals.

#### New Zealand:

- 1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
- 2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
- 3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
- 4. Transport of Dangerous goods on land NZS 5433:2012
- 5. HSW (Hazardous Substances) Regulations 2017

#### Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 15 November 2018 Review Date: 15 November 2023

Product Name: Staybound Epoxy Glue Base
Date of SDS: 15 November 2018

Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz